



# CAG 501B – LEVEL IIIA HELMET




## Features & Specifications

- US Army ACH Geometry
- Shell constructed of a proprietary blend of Aramid and Composite Materials
- NIJ Level IIIA 0108.01/0106.01
- Frag protection: 17 grain B50 > 2130 f/s (650 m/s) in accordance with MIL-STD-662F
- 9mm BFD/Trauma up to 1" at NIJ IIIA velocity on average
- Performs under temperature between 160° F (71° C) and -60° F (-51° C); Performs after 3 hours sea water immersion

## Shell & System Information

- Shell Thickness: 0.4" (± 0.1") / 10 mm (± 2.5mm)
- Finished Shell Nominal Weight\*:
  - Medium 2.7 lbs. / 1.22 kg; Large 3.2 lbs. / 1.45 kg;
  - X Large 3.4 lbs. / 1.55 kg
- Finished Helmet Nominal Weight\*\*:
  - Medium 3.1 lbs. / 1.4 kg; Large 3.2 lbs. / 1.45 kg
  - X-Large 3.4 lbs. / 1.55 kg
- Fully Loaded High Cut Nominal Weight\*\*\*:
  - Medium 3.2 lbs. / 1.45 kg; Large 3.3 lbs. / 1.48 kg
  - X-Large 3.5 lbs. / 1.58 kg

## Available Colors



FOLIAGE GREEN

OLIVE GREEN

SNIPER BLACK

DESERT TAN

COYOTE BROWN

## Available Cuts



HIGH-CUT

MID-CUT

REGULAR-CUT

## Environmental Performance

- Shock Absorption
- Resistance For Penetration
- Advanced Boltless Adhesive System

## Compatibility & Add-Ons

- Universal Side-Rails
- NVG Mount
- Operational Loop System
- Counterweight
- Camouflage Cover
- Carrying Bag
- Strap Extenders
- Visor/Goggles
- Gas Mask
- Communications/Ear Protection